

Cryptography

Lecture 3: Indistinguishability & Limits of Perfect Secrecy

October 30, 2026

1

Perfectly Secret Encryption

Notes

- Use consistent variable naming (messages, keys, ciphertext)
- Drop distribution marker — write $P(m)$ instead of $P_M(m)$
- Utilize usual probability notation — $P(m, c)$ for joint probability
- Assume message & key selection is independent

$$P(k, m) = P(k) \cdot P(m)$$

- Then

$$P(c) = \sum_{k \in K, m \in M} P(k, m) \cdot P[c \leftarrow \text{enc}_k(m)]$$

and in perfectly secret encryption scheme $\mathcal{E}$ for any message $m' \in M$

$$P(c) = O_{\mathcal{E}}(c, m') = \sum_{k \in K} P(k) \cdot P[c \leftarrow \text{enc}_k(m')]$$

2

Perfectly Secret Encryption

§2.7 Lemma

Encryption scheme $\mathcal{E}$ is perfectly secret if and only if in every scenario $(\mathcal{E}, P_M)$ we have $P(m | c) = P(m)$ for all messages $m \in M$ and possible ciphertexts $c \in C$ with $P(c) \neq 0$

Proof (1/2)

($\Rightarrow$) Let $P_M: M \rightarrow [0, 1]$, $m, m' \in M$, and $c \in C$ with $P(c) \neq 0$

$$\begin{aligned} P(m | c) &= \frac{P(m, c)}{P(c)} = \frac{\sum_{k \in K} \overbrace{P(k) \cdot P(m) \cdot P[c \leftarrow \text{enc}_k(m)]}^{=P(m, c)}}{\underbrace{O_{\mathcal{E}}(c, m')}_{=P(c)}} \\ &= P(m) \cdot \frac{\sum_{k \in K} P(k) \cdot P[c \leftarrow \text{enc}_k(m)]}{O_{\mathcal{E}}(c, m')} = P(m) \cdot \frac{O_{\mathcal{E}}(c, m)}{O_{\mathcal{E}}(c, m')} \end{aligned}$$

3

Perfectly Secret Encryption

Proof (2/2)

($\Leftarrow$) Let $c \in C$ and $m, m' \in M$. Consider distribution $P_M: M \rightarrow [0, 1]$ such that $P_M(m) = P_M(m') = \frac{1}{2}$ and $P_M(m'') = 0$ otherwise. First suppose that $P(c) = 0$. Then

$$P(k) \cdot P[c \leftarrow \text{enc}_k(m)] = 0 = P(k) \cdot P[c \leftarrow \text{enc}_k(m')]$$

for all $k \in K$. Hence $O_{\mathcal{E}}(c, m) = O_{\mathcal{E}}(c, m')$ as required.

Otherwise $P(c) \neq 0$ and we prove that $P(c) = O_{\mathcal{E}}(c, m'')$ for all $m'' \in \{m, m'\}$, which also proves $O_{\mathcal{E}}(c, m) = O_{\mathcal{E}}(c, m')$

$$P(c) = \frac{P(m'', c)}{P(m'' | c)} = \frac{\sum_{k \in K} P(k) \cdot \cancel{P(m'')} \cdot P[c \leftarrow \text{enc}_k(m'')]}{\cancel{P(m'')}} = O_{\mathcal{E}}(c, m'')$$

□

4

One-Time Pad

§2.8 Example (One-time pad; Vernam 1917)

Let $\ell \in \mathbb{N}$ and $K = M = C = \{0, 1\}^\ell$. Length ℓ **one-time pad** is given by

- Key generation $P_K(k) = 2^{-\ell}$ for all $k \in K = \{0, 1\}^\ell$
(uniform selection from key space of all keys of length ℓ)
- Encryption $\text{enc}: K \times M \rightarrow C$ with $K = M = C = \{0, 1\}^\ell$

$$\text{enc}_k(m_1, \dots, m_\ell) = (m_1 \oplus k_1, \dots, m_\ell \oplus k_\ell)$$

with $k = (k_1, \dots, k_\ell)$ (bitwise XOR of message & key)
- Decryption $\text{dec} = \text{enc}$

Gilbert Sandford Vernam (* 1890; † 1960)

- US engineer at AT&T Bell Labs
- Cipher patented in 1919; used by allies in WW2
- Shannon (also at Bell Labs) proved it unbreakable



5

One-Time Pad

Illustration

m	1	1	0	1	1	1	1	1	0	1	1	1	0	0	1	1	0	0	0	1	1	0
k	0	1	0	0	1	1	1	1	0	1	1	1	1	0	1	0	1	0	1	1	1	0
$\text{enc}_k(m)$	1	0	0	1	0	0	0	0	1	1	0	0	0	0	1	1	0	1	1	1	0	1
k	0	1	0	0	1	1	1	1	0	1	1	1	1	0	1	0	1	0	1	1	1	0
$\text{dec}_k(m)$	1	1	0	1	1	1	1	1	0	1	1	1	0	0	1	1	1	0	0	0	1	1

Notes

- Correctness of one-time pad obvious $(m \oplus k) \oplus k = m \oplus (k \oplus k) = m$
- Key length = message length (biggest drawback)

6

One-Time Pad

§2.9 Theorem

(Length ℓ) One-time pad encryption scheme (§2.8) is perfectly secret

Proof

Let $c \in C$ and $m, m' \in M$. Since key distribution is uniform, we just prove

$$\sum_{k \in K} P[c \leftarrow \text{enc}_k(m)] = \sum_{k \in K} P[c \leftarrow \text{enc}_k(m')]$$

$P[c \leftarrow \text{enc}_k(m)]$ is 1 for $k = m \oplus c$ and 0 otherwise. Hence left-hand side is 1 and with same argument also right-hand side is 1. $\square$

7

One-Time Pad

Notes

- XOR removes message bias
(ciphertexts uniformly distributed for any message distribution)
- In general $k \leftarrow U_n$; $m \leftarrow P_M$; $c = k \oplus m$ yields uniformly distributed c
($k \leftarrow U_n$ means draw k from uniform distribution on $\{0, 1\}^n$)
- XOR used in modern cryptography for this reason

Question

- Are uniformly distributed ciphertexts needed for perfect secrecy?

8

Recall

Definition (§2.5 Perfectly secret)

Encryption scheme $\mathcal{E} = (\text{gen}, \text{enc}, \text{dec})$ is **perfectly secret** if $O_{\mathcal{E}}(c, m) = O_{\mathcal{E}}(c, m')$ for all messages $m, m' \in \mathcal{M}$ and ciphertexts $c \in \mathcal{C}$

Notes

- One-time pad is perfectly secret
- Reveals no information about message from ciphertext (Lemma §2.7) (length of message already part of scheme)
- Protocol-based (two-player game) characterization follows (as preparation for later definitions)
- Stateful algorithms
= algorithms with persistent memory, aware of protocol step

9

Perfect Indistinguishability

§3.1 Definition (Perfect indistinguishability game)

Let $\mathcal{E} = (\text{gen}, \text{enc}, \text{dec})$ be encryption scheme and $\mathcal{A}$ stateful probabilistic algorithm. **Adversarial indistinguishability game** $\text{PrivK}^{\text{one}}(\mathcal{E}, \mathcal{A})$ is


- 1 $\mathcal{A}$ selects messages $m_0, m_1 \in \mathcal{M}$
- 2 $k \leftarrow \text{gen}()$, uniform random bit $b \in \{0, 1\}$
 $c \leftarrow \text{enc}_k(m_b)$ sent to $\mathcal{A}$ (challenge ciphertext)
- 3 $\mathcal{A}$ outputs bit $b' \in \{0, 1\}$
- 4 Return 1 if $b = b'$ ($\mathcal{A}$ wins)
Return 0 otherwise

Notes

- 1 Adversary selects messages to be distinguished
- 2 System encrypts randomly selected message with random key
- 3 Adversary predicts which message was encrypted based on ciphertext
- 4 Adversary wins if prediction correct

10

Perfect Indistinguishability



11

Perfect Indistinguishability

Standard function reformulation

Definition (§3.1 Perfect indistinguishability game)

Let $\mathcal{E} = (\text{gen}, \text{enc}, \text{dec})$ be encryption scheme, $m_0, m_1 \in \mathcal{M}$ messages, and $f: \mathcal{M}^2 \times \mathcal{C} \rightarrow \{0, 1\}$. **Adversarial indistinguishability game** $\text{PrivK}^{\text{one}}(\mathcal{E}, m_0, m_1, f)$ is

- 1 $k \leftarrow \text{gen}()$, uniform random bit $b \in \{0, 1\}$
 $c \leftarrow \text{enc}_k(m_b)$
- 2 $b' \leftarrow f(m_0, m_1, c)$
- 3 Return 1 if $b = b'$ (f wins)
Return 0 otherwise

12

Perfect Indistinguishability

§3.2 Definition (Perfectly indistinguishable)

Encryption scheme $\mathcal{E} = (\text{gen}, \text{enc}, \text{dec})$ is **perfectly indistinguishable** if for every probabilistic algorithm $\mathcal{A}$

$$\mathbb{P}[\text{PrivK}^{\text{one}}(\mathcal{E}, \mathcal{A})] = \frac{1}{2}$$

Notes

- $\mathbb{P}[\text{PrivK}^{\text{one}}(\mathcal{E}, \mathcal{A})]$ = probability that $\mathcal{A}$ wins game
- $\mathcal{A}$ can trivially win 50% of games by returning uniform random bit b'
- Perfectly indistinguishable = $\mathcal{A}$ cannot do better (or worse)

13

Perfect Indistinguishability

Standard function reformulation

Definition (§3.2 Perfectly indistinguishable)

Encryption scheme $\mathcal{E} = (\text{gen}, \text{enc}, \text{dec})$ is **perfectly indistinguishable** if for all $m_0, m_1 \in \mathcal{M}$ and functions $f: \mathcal{M}^2 \times \mathcal{C} \rightarrow \{0, 1\}$

$$\mathbb{P}[\text{PrivK}^{\text{one}}(\mathcal{E}, m_0, m_1, f)] = \frac{1}{2}$$

Notes

- We stick to stateful algorithms in following
- Cleaner grouping of selections (avoid quantifiers on m_0, m_1)

14

Perfect Indistinguishability

Example: Shift cipher $\mathcal{E}$

- Adversary $\mathcal{A}$ selects messages $m_0 = aa$ and $m_1 = ab$
- Adversary $\mathcal{A}$ receives ciphertext $c = c_1 c_2$
 - ▶ Returns 0 if $c_1 = c_2$
 - ▶ Returns 1 otherwise

$$\begin{aligned}\mathbb{P}[\text{PrivK}^{\text{one}}(\mathcal{E}, \mathcal{A})] &= \frac{1}{2}\mathbb{P}[\text{PrivK}^{\text{one}}(\mathcal{E}, \mathcal{A}) \mid b = 0] + \frac{1}{2}\mathbb{P}[\text{PrivK}^{\text{one}}(\mathcal{E}, \mathcal{A}) \mid b = 1] \\ &= \frac{1}{2}\mathbb{P}[c_1 = c_2 \mid b = 0] + \frac{1}{2}\mathbb{P}[c_1 \neq c_2 \mid b = 1] \\ &= \frac{1}{2} + \frac{1}{2} = 1 > \frac{1}{2}\end{aligned}$$

→ Shift cipher not perfectly indistinguishable

15

Perfect Indistinguishability

§3.3 Theorem

Encryption scheme is perfectly secret iff it is perfectly indistinguishable

Proof (1/2)

(→) Let $\mathcal{A}$ be prob. algorithm, $r \in R$, and $m_0, m_1 \in \mathcal{M}$ selected messages. Moreover, let $C_b = \{c \in \mathcal{C} \mid \mathcal{A}_r(c) = b\}$ for all $b \in \{0, 1\}$. Obviously $\mathcal{C} = C_0 \cup C_1$. ($\mathcal{A}_r$ is de-randomized version of $\mathcal{A}$)

$$\begin{aligned}\mathbb{P}[\text{PrivK}^{\text{one}}(\mathcal{E}, \mathcal{A}_r)] &= \frac{1}{2}\mathbb{P}[\mathcal{A}_r(c) = 0 \mid b = 0] + \frac{1}{2}\mathbb{P}[\mathcal{A}_r(c) = 1 \mid b = 1] \\ &= \frac{1}{2}\left(\sum_{c \in C_0} O_{\mathcal{E}}(c, m_0)\right) + \frac{1}{2}\left(\sum_{c \in C_1} O_{\mathcal{E}}(c, m_1)\right) \\ &= \frac{1}{2}\sum_{c \in \mathcal{C}} O_{\mathcal{E}}(c, m_0) = \frac{1}{2}\end{aligned}$$

16

Perfect Indistinguishability

Proof (2/2)

($\leftarrow$) Suppose that $\mathcal{E}$ is not perfectly secret. Then there exist messages $m_0, m_1 \in \mathcal{M}$ and ciphertext $c \in \mathcal{C}$ such that $O_{\mathcal{E}}(c, m_0) \neq O_{\mathcal{E}}(c, m_1)$. Consider adversary $\mathcal{A}$ that selects messages m_0, m_1 and then receives ciphertext $c' \in \mathcal{C}$. If $c = c'$, then $\mathcal{A}$ returns $b' = 0$. Otherwise it returns uniform random bit b' .

$$\begin{aligned} P[\text{PrivK}^{\text{one}}(\mathcal{E}, \mathcal{A})] &= \frac{1}{2}P[b' = 0 \mid b = 0] + \frac{1}{2}P[b' = 1 \mid b = 1] \\ &= \frac{1}{2} \left(\frac{1}{2}P[c' \neq c \mid b = 0] + P[c' = c \mid b = 0] \right) + \frac{1}{4}P[c' \neq c \mid b = 1] \\ &= \frac{1}{4}(1 - O_{\mathcal{E}}(c, m_0)) + \frac{1}{2}O_{\mathcal{E}}(c, m_0) + \frac{1}{4}(1 - O_{\mathcal{E}}(c, m_1)) \\ &= \frac{1}{4} \left(2 + \underbrace{O_{\mathcal{E}}(c, m_0) - O_{\mathcal{E}}(c, m_1)}_{\neq 0} \right) \neq \frac{1}{2} \end{aligned}$$

17

Limits of Perfect Secrecy

§3.4 Theorem

If $\mathcal{E} = (\text{gen}, \text{enc}, \text{dec})$ is perfectly secret, then $|K| \geq |\mathcal{M}|$

Proof

By contraposition: Let $|K| < |\mathcal{M}|$ and thus K is finite. Clearly, $|K| \geq 1$, so take $k \in \text{ran}(\text{gen})$. Similarly, take $r \in R$ and $m \in \mathcal{M}$ arbitrarily. Let $c = \text{enc}(r, k, m)$, so $P(k) \cdot P[c \leftarrow \text{enc}_k(m)] \neq 0$. Select $\mathcal{M}' \subseteq \mathcal{M}$ of size $|K| + 1$ arbitrarily such that $m \in \mathcal{M}'$. Consider scenario $(\mathcal{E}, P_{\mathcal{M}'})$ with uniform distribution on $\mathcal{M}'$. Then $P(k) \cdot P(m) \cdot P[c \leftarrow \text{enc}_k(m)] \neq 0$ and hence $P(c) \neq 0$. Let $\mathcal{M}'' = \{\text{dec}_{k'}(c) \mid k' \in K\}$. Obviously $|\mathcal{M}''| \leq |K| < |\mathcal{M}'|$. Hence there exists $m' \in \mathcal{M}' \setminus \mathcal{M}''$.

$$P(m' \mid c) = 0 \neq \frac{1}{|K| + 1} = P(m')$$

so $\mathcal{E}$ is not perfectly secret by Lemma §2.7.

18

Limits of Perfect Secrecy

Consequences

- Perfect secrecy requires at least as many keys as there are messages ($\rightarrow$ perfect secrecy unpractical)
- One-time pad achieves optimal $|K| = |\mathcal{M}|$

Questions

- Can keys be reused?
(Is one-time pad still perfectly secret if multiple messages are encrypted with the same key?)
- Are there other optimal perfectly secret encryption schemes?

19

Limits of Perfect Secrecy


§3.5 Theorem (Shannon's theorem)

Let $\mathcal{E} = (\text{gen}, \text{enc}, \text{dec})$ encryption scheme with $|K| = |\mathcal{M}| = |\mathcal{C}| = \ell \in \mathbb{N}$. Then $\mathcal{E}$ is perfectly secret iff

- $P_K(k) = \ell^{-1}$ for every $k \in K$ (uniform key distribution)
- For every $m \in \mathcal{M}$ and $c \in \mathcal{C}$ there exists unique $k \in K$ such that $P[c \leftarrow \text{enc}_k(m)] \neq 0$
(det. encryption and $\text{enc}(\cdot, m): K \rightarrow \mathcal{C}$ bijective for every $m \in \mathcal{M}$)

Claude Elwood Shannon (* 1916; † 2001)

- US mathematician & electrical engineer
- Father of information theory
- Alfred-Noble-laureate (1939), but not Nobel-laureate (different Alfred)



© Konrad Jacobs

20